

## Series VEP3 High Precision Micro Flush Diaphragm Pressure Transmitter

### Feature

- Liquid and gas media compatible with SST304 or 17-4PH
- Miniature design (body ø11 mm)
- Sturdy flush diaphragm Impact resistance, easy to clean
- Weather-proof rate up to IP68



### Specification

- Ranges from 3.5 to 700 bar(50 to 10,000 psi)
- Combined linearity & hysteresis <0.25%
- Operating temperature -40°...150°C(300°F)
- M8X1,M6X1 Variety of pressure ports Optional

### Accuracy

±0,25 %FS, ±0,5 %FS

### Total error band

±0,5 %FS @ 0...70 °C

### Pressure ranges

0...10 to 0...500 bar

### Applications

- Motorsports
- Downhole Exploration
- Sturdy flush diaphragm
- Hydraulic Pressures
- Impact resistance, easy to clean
- Transportation

# Series VEP3 High Precision Micro Flush Diaphragm Pressure Transmitter

## Standard pressure ranges

### Standard Ranges


Measuring Method	Range (psi)	Range (Bar)	Gage	Sealed	Absolute	Compound	
	0 to 500	0 to 35	•			•	
	0 to 1000	0 to 70	•			•	
	0 to 1500	0 to 100	•			•	
	0 to 2250	0 to 150	•			•	
	0 to 3000	0 to 200	•			•	
	0 to 5000	0 to 350	•			•	
	0 to 7500	0 to 500	•			•	
	0 to 10000	0 to 700	•			•	

## Performance

### Pressure

PARAMETERS	MIN	TYP	MAX	UNITS	NOTES
Accuracy (Combined Non-linearity, hysteresis, and repeatability)	-0.5	±0.25	0.5	%F.S. BFSL	@ 25°C
Zero Error	-0.5	±0.5	0.5	%F.S. BFSL	@25°C
Full Scale Error	-0.5	±0.5	0.5	%F.S. BFSL	@25°C
Isolation, Body to any Lead	100			MΩ	@250VDC
Dielectric Strength			2	mA	@500VAC, 1min
Pressure Cycles	1X10 <sup>7</sup>			0-FS Cycles	
Proof Pressure	2 X				Rated
Burst Pressure	3X		20k psi		Rated
Long Term Stability (1 year)	-0.25		0.25	%F.S.	
Total Error Band	-1.5	±1.0	1.5	%F.S.	Over compensated temperature range
Compensation Temperature	-20		85		
Operating Temperature	-40		+150	°C	Except cable 105°C MAX
Storage Temperature	-40		+150	°C	Except cable 105°C MAX
Load Resistance (RL)	RL > 100k			Ω	Voltage Output
Load Resistance (RL)	< (Supply Voltage -9V) / 0.02A				Ω
Current Consumption			10	mA	Current Output
Rise Time (10% to 90%)	<2ms (Voltage Output); <3ms (Current Output); Without Snubber				Voltage Output
Pressure Port Material	316L				

Shock	50g, 11msec Half Sine Shock per MIL-STD-202G, Method 213B, Condition A
Vibration	±20g, MIL-STD-810C, Procedure 514.2-2, Curve L



CODE	PRESSURE PORT TYPE	
	PORT	
1		G1/4 JIS B2351
2		M5
3		M6
4		M8
5		M14x1.5 mm ISO 6149-2
6		1/8-27 NPT
7		M12x1.5 mm ISO 6149-2
8		M10x1.0 mm ISO 6149-2
9		G1/4 DIN 3852 FORME GASKET DIN3869-14 NBR

CODE	CONNECTION TYPE	DIM C (MAX)
1	Cable	1.97 [50.0]
2	Packard A	2.10 [53.5]
3	Packard B	2.10 [53.5]
4	M12	1.71 [43.5]
5	FORMA	1.93 [49.0]
6	FORM C	1.97 [50.0]
7	AMP	2.52 [64.0]

CODE	OUTPUT SIGNAL	SUPPLYVOLTAGE
	0.5-4.5V	5±0.25V
1	Ratiometric	Protected to 16V
2	1-5V	8-36V
3	4-20mA	9-36V
4	0-5V	8-36V
5	0-10V	13-36V
6	1-6V	8-36V
7	0.5-4.5V	7.5-36V

The following wiring definition is commonly used in Mainland China and will need to be determined individually with the European, the UK and the US customers.

CURRENT OUTPUT WIRING				
CONNECTION	+SUPPLY	-SUPPLY	NC. PINS	P REF VENT
Packard, A	A	B	C	Hole Through Connector
Packard, B	B	A	C	
FORM A	1	2	3,4	
M12	1	2	3,4	
CABLE	RED	BLK		Pipe In Cable
VOLTAGE OUTPUT WIRING				
CONNECTION	+SUPPLY	+OUTPUT	COMMON	NC. PINS
Packard, A	A	C	B	Hole Through Connector
Packard, B	B	C	A	
FORM A	1	3	2	
M12	1	3	2	
CABLE	RED	WHT	BLK	Pipe In Cable

#### Compensated Temperature:

This is the temperature range within which the product will produce an output proportional to pressure, while remaining within the specified performance limits.

#### Operating Temperature:

This is the temperature range within which the product will produce an output proportional to pressure, but it may not remain within the specified performance limits.

#### Storage Temperature:

This is the temperature range within which the product can be safely stored without pressure applied or power input, while still maintaining its rated performance. Exposure to temperatures beyond this range may cause permanent damage to the product.

All configurations are designed with protection against reverse supply voltage and output short circuits.

#### CE Compliance (just for reference)

EN 55022 Emissions Class A & B  
 IEC 61000-4-2 Electrostatic Discharge Immunity (8kV contact/15kV air)  
 IEC 61000-4-3 Radiated, Radio-Frequency Electromagnetic Field Immunity (10V/m, 80M-1GHz)  
 IEC 61000-4-4 Electrical Fast Transient Immunity (1kV)  
 IEC 61000-4-5 Surge Immunity (V+ to V-: ±2kV/42Ω; L to Case: ±1kV/12Ω; V- to V0: ±1kV/42Ω)  
 IEC 61000-4-6 Immunity to Conducted Disturbances Induced by Radio Frequency Fields (150K~80MHz, 10V level for voltage output models, 3V level for current output model)  
 IEC 61000-4-9 Pulse Magnetic Field Immunity (100A/m peak)  
 For all CE compliance tests, max allowed output deviation ±1.5 %F.S. (Just Factory Testing)

#### Weather-Proof Rating


Connection	P Code
Packard A / B	IP66
Cable	IP67
M12	IP67
Form A	IP65
Form C	IP66
AMP	IP66


## Mechanical data

Materials in contact with media

Pressure connection	Stainless steel 17-4 PH
Pressure transducer diaphragm	Stainless steel SUS 316L
Pressure transducer seal (internal)	None
Pressure connection seal (external)	None, metallically sealed

## Electrical connections

Round plug	2-wire	3-wire	Valve plug	2-wire	3-wire
M12 x 1	4...20 mA	0...10 V	Form A	4...20 mA	0...10 V
	1 +Vs 2 n.c. 3 OUT/GND 4 n.c.	1 +Vs 2 n.c. 3 +OUT 4 GND		1 n.c. 2 OUT/GND 3 +Vs 4 Case	1 GND 2 +OUT 3 +Vs 4 Case



## Series VEP3 – Ordering Information

Example	VEP30341015500PG	VEP3	3	4	1	0	1	5	500P	G
<b>Model Code VEP3 Pressure Transducer</b>										
<b>Output</b>	1	0.5-4.5V RATIO METRIC								
	2	1-5V								
	3	4-20mA								
	4	0-5V								
	5	0-10V								
	6	1-6V								
	7	0.5-4.5V								
	x	Customization								
<b>Connection</b>	1	Cable								
	2	Packard A								
	3	Packard B								
	4	M12								
	5	FORM A								
	6	FORM C								
	7	AMP								
	8	Customization								
<b>Port Material</b>	1	304Screw+ 17-4 Diaphragm								
	2	17-4 Integral Screw								
	x	Customization								
<b>Snubber</b>	0	No Snubber								
	1	With Snubber								
<b>Label</b>	0	No Label (OEM)								
	1	AdhesiveLabel								
	2	Laser Marking								
<b>Pressure Port</b>	1	G1/4 JIS B2351								
	2	M20 x 1.5								
	3	1/4-18 NPT								
	4	7/16-20UNF FEMALE SAE								
	5	M14 x 1.5								
	6	1/8-27 NPT								
	7	M12 x 1.5								
	8	M10 x 1.0								
	9	G1/4 DIN 3852								
	A	G3/8 JIS B2351								
	x	Customer Specia								
<b>Pressure Range</b>	B	Bar								
	M	Mpa								
	P	PSI								
	K	Kpa								
<b>Pressure Type</b>	G	Gauge								
	S	Sealed (>500PSI)								
	C	Compound								